


T5 LED Glass Tube (Internal Driver)

Size chart



Packaging

- ① 60g Paper Sleeves (Optional Color Print)
- ② Corrugated Card Boxes (Pinch or Cover Style with Optional Color Print)
- ③ 350g White Boxes (Optional Labeling & Color Printing)
- ④ Paper Tubings + PE Bags (Optional Labeling)
- ⑤ Air Cushions
- ⑥ Foam Protection (Board & Racking)



MODEL (PROFESSIONAL)	DIMENSION D*L(mm)	POWER	INPUT VOLTAGE	LUMEN EFFL	COLOR TEMP	CRI	PF	PCS/CTN	CTN MEAS
SABA T5G-P5	16*288	5W	85-265V	110-130lm/W	4100K 6000K	70/80	>0.9	100	33.5*28*5*28
SABA T5G-P9	16 * 549	9W	85-265V	110-130lm/W	4100K 6000K	70/80	>0.9	100	59.5*28.5*28
SABA T5G-P12	16 * 849	12W	85-265V	110-130lm/W	4100K 6000K	70/80	>0.9	50	89.5*28.5*15
SABA T5G-P16	16 * 1000	16W	85-265V	110-130lm/W	4100K 6000K	70/80	>0.9	50	105.5*28.5*15
SABA T5G-P18	16 * 1149	18W	85-265V	110-130lm/W	4100K 6000K	70/80	>0.9	50	119.5*28.5*15

SABA LED tubes are durable, efficient and reliable due to the superior components used and the excellent driver cooling method. The glass tubes allows wider beam angle of 330 degree. SABA T5 LED tubes are equipped with built-in driver, this allows much easier installation, maintenance and retrofit of LED tubes compared to those with external driver.

All product specification and design may vary, due to new technology, without prior notice.